



Wind Turbines | Electric Cabinets | Transformers | Others

Revolutionary Fire Suppression Systems



Made in Germany



detexline
electric

ROBUST - PATENTED - UNIQUE!

*The need for simplicity and robustness, makes
Detexline Electric the leading solution for
demanding conditions Fire Suppression*

Reliability and low maintenance.
Trusted by leading wind turbine manufacturers





Efficiency & Robustness



The power of liquid extinguishing agent

A large amount of fine droplets of liquid agent is sprayed through the special patented nozzles forming a huge cooling reaction surface. Thus, the fire will be quickly deprived of thermal energy, leading to a rapid temperature drop. The cooling effect breaks the reaction necessary to support combustion.

In addition, after the entire extinguisher has been dispensed, nitrogen propellant gas will be discharged from the patented container, resulting in a hybrid suppression system, also ensuring fire suffocation.

100% Stainless Steel
No plastics in the core system



LIQUID FIRES

Fuel, lubricant and hydraulic fluids

SOLID FIRES

Plastic, rubber, wood, sawdust, wires, cables

ELECTRICAL FIRES

Electrical cabinets, substations, transformers and other equipment





Fully Pneumatic self-contained / no corrosion

Perfect for Off-shore wind turbines

Thanks to maintenance-free and stainless steel components.



Multiple configurations with One system

**Effective on:
Open doors / ventilated cabinets**



Single-line system (det-ex)

Detection and extinguishing in a single pipe line.



No Pressure

The extinguishing agent container is made of stainless steel and is pressure-free in the operating state. The tubing is also pressureless.



No Electricity

No electricity needed in the system.



10 Years - No parts change

Long savings - durable and resistant parts.



Ultra-fast detection

Response speed: Ultra Fast Response RTI 12. False alarm proof. Based on "temperature" parameter for pneumatic activation.



Operation temperature range: -50°C to 80°C

Prepared for extreme climates, whether in the desert or in the mountains.



Capable of working in extreme conditions

Shock and vibration resistant.



Stainless steel

Precision manufacturing - highly durable stainless steel.



Very low maintenance

Due to the absence of pressure and simplicity, maintenance routines are practically only visual.




Fully Mechanical / Pneumatic

The entire system is self-contained. It does not require manual operations and does not depend on external controls, such as control panels or electrical detectors.

Possibility of multiple temperature ranges in a single system.
57 °C | 68 °C | 79 °C | 93 °C | 110 °C | 141 °C | 182 °C | 230 °C | 260 °C

Operates in highly ventilated places and in open spaces





Long-Term Savings

Factors that make Detexline the most economical system

Almost maintenance-free for 10 years:

No need for the usual annual maintenance as it is not pressurized!

No False Alarms:

Patented, accurate and reliable detection system.

Make your own maintenance:

Your own staff - no need for external companies.

It can be reinstalled in different vehicles:

Easy and fast installation.

How it Works

The detexline tank and piping network are not pressurized. The SPY detectors will be activated by thermal detection, thus releasing the pressure in the pipeline and cylinder control valve, which in turn will trigger the release of the extinguishing agent. Fine spray nozzles will disperse the Tiborex Absolute providing the cooling effect and effectively extinguishing fires within the first few seconds. It can be manually activated remotely. An alarm and test button can be installed.

Name	detexline Electric
Temperature Range	-50°C / -30°C to 80°C
Detection Technology	Rise of Pressure
Detection and External Line	One integrated line
System Pressure	No pressure
Detection Technology	SPY detection element - Stainless steel
Trigger Temperature	Glass ampoule, 9 independent temperatures
Life of Detectors	10 years
Nozzle Type	S1
Extinguishing Agent	Tiborex Absolute
Extinguishing Agent Volume	4, 7, 14, 24L
Extinguishing Technology	Fine spray technology
Extinguishing Container (pressure)	Pressureless (Sealed Cartridge)
Product Material	Stainless steel
Alarm Signal Switch	Yes
Maintenance Inspection	Annually
Parts Replacement Duration	10 years

Certifications for protectfire various systems:





System Components

SPY thermo-pneumatic detector



Unique patented detector
No electricity required
High-finish stainless steel
Response speed: Ultra Fast Response RTI 12
Available detection temperatures:
-57°C -68°C -79°C -93°C -110°C -141°C -182°C -230°C 260°C



Directional Valve

Ability to redirect the extinguishing agent only to the place that activated the detector. In this way, the extinguishing agent will be directed more accurately and without waste.




Compact
Fast to Install



Fine-Spray Nozzles

Unique patented nozzle solution
Quick and easy to install - Reduces installation time by ~70%.
Very small - Virtually fits anywhere
Stainless steel
S1 factor 0.5 - Fine spray technology
Up to 90° spray pattern
High quality, heavy-duty nozzle caps

Pneumatic Manual Actuator



Unique patented pneumatic activation system
Stainless steel
Safety locking system
Argon gas activation



Extinguishing Agent Tank

Patented - Unique Pneumatic Release System
Can be placed in any position!
Stainless steel with electrostatic paint finish Ral3000
Patented - Stainless steel actuation system

Liquid Agent: Tiborex Absolute - exclusive protectfire agent
Effective against liquid, solid and grease fires.



Extinguishing Agents Comparison

	TiboRex Absolute	Water	Foam	Powder	Gas
Fast Temperature Reduction	+	-	-	-	-
Surface Blanketing	+	-	+	-	-
Quenching Effect	+	-	+	-	+
Fine-Spray Technology	+	+	-	-	-
Fluorine Free	+	+	-	-	+
Temperature Range -50°C to +80°C	+	-	-	+	-
Danger to Persons	+	+	-	-	-

Ultrafast extinguishing

Only small amounts of extinguishing agent required. Tiborex rapidly delivers a huge cooling power. The object to be protected remains almost undamaged.

Ultrafast cooling

Enormous reduction of surface temperature. Avoidance of re-ignition. Reduced effect of fire. Quick interruption of combustion process.

The cooling effect

The enormous cooling effect of Tiborex Absolute is mainly based on **two physical properties:**

Quenching effect

Rapid removal of thermal energy therefore removing heat, hence no combustion or fire in hidden cavities.

Blanketing fat and oil fires

When mineral, animal or vegetable fats and oils burn, Tiborex Absolute uses chemical reactions to form a closed, gas-proof protective layer quenching the fire and protecting the hot fat or oil from re-ignition by cooling them down very quickly.

Cooling effect due to water evaporation: The fine-spray nozzles developed specially for Tiborex Absolute produce very fine droplets, smaller than 100µm, when discharging the extinguishing agent. As a result, ultra-fast evaporation of the liquid share in the extinguishing agent is achieved. Due to the required enthalpy of evaporation of 2.26 MJ/kg (equivalent to 1 litre of water) energy is extracted from the burning object in a minimum of time and it cools down substantially.

Residue monitoring and guaranteed quality

Residues of the extinguishing agent on the object can be identified with the help of ultraviolet light. A chemical analysis (DNA) can verify and confirm that the original Tiborex Absolute was used.


Environmental friendliness

Ecological and 100% fluorine-free extinguishing agent. Biodegradable. Non toxic to humans and animals.


Cooling effect due to sublimation: During the evaporation of the aqueous phase some of Tiborex Absolute's main components form crystalline structures. With the still existing combustion temperature, these solid structures change from the crystalline phase to a gaseous phase. The enormous enthalpy of evaporation (heat) required for this amounts to 7.23 MJ/kg.

3 stages fire suppression

1 Cooling Effect Fine Spray Droplets that penetrate fire



2 Oxygen Suffocation by evaporation



3 Ultra Cooling through Sublimation Layering with solid crystals that convert to gas

